

TABLE OF CONTENTS

CHAPTER 1	Introduction	1
1.1	Background.....	1
1.1.1	Distributed Coordination Function (DCF)	2
1.1.2	RTS/CTS and NAV mechanism.....	3
1.1.3	Ad Hoc Wireless Networks	5
1.1.4	Quality of Service.....	7
1.1.5	MANET QoS.....	7
1.2	Motivation	10
1.3	Organization	11
CHAPTER 2	Related Work.....	12
2.1	Bandwidth Reservation	12
2.1.1	CDMA over TDMA.....	13
2.2	Path Bandwidth Calculation.....	14
2.2.1	Bandwidth Calculation using Link/Path Bandwidth Information	15
2.3	Routing	18
2.3.1	Table Driven Routing Protocol: DSDV [13]	18
2.3.2	The On-Demand Routing Protocol: AODV [26].....	19
2.4	SWAN [28]	22
CHAPTER 3	The Proposed Call Admission Control Scheme	23

3.1	Architecture	23
3.2	Path Bandwidth Calculation.....	25
3.2.1	Single Hop	26
3.2.2	Two Hop	29
3.2.3	Multi Hop	31
3.3	Bandwidth Routing.....	32
3.3.1	Call Admission Control Policy	34
3.3.2	Contribution Discussion	34
CHAPTER 4 Simulation Results		36
4.1	Parameters	36
4.1.1	Parameters of IEEE 802.11 MAC	37
4.1.2	Traffic Characteristics	37
4.1.3	Calculation of each node's idle percentage	38
4.2	Scenarios and Results.....	38
4.2.1	Single Hop	39
4.2.2	Two Hop	46
4.2.3	Multi Hop	52
4.2.4	Integrated Scenario	57
CHAPTER 5 Conclusions and Future Work.....		61

LIST OF TABLES

Table 3.1: Routing Table at Node A.....	33
Table 4.1: Parameters of IEEE 802.11 MAC.....	37
Table 4.2: Traffic Characteristics.....	38

LIST OF FIGURES

Figure 1-1: Basic access method.....	2
Figure 1-2: Backoff procedure.	3
Figure 1-3: RTS/CTS/data/ACK and NAV setting.	5
Figure 1-4: Ad Hoc Wireless Networks.	6
Figure 1-5: Bandwidth Affection in Ad Hoc Wireless Networks.	8
Figure 1-6: IEEE 802.11e protocol.	9
Figure 2-1: CDMA over TDMA.	13
Figure 2-2: Clustered multi-hop wireless network.	14
Figure 2-3: Transmission Time Scale, Frames and Time Slots.....	15
Figure 2-4: Bandwidth information calculation overview.	16
Figure 2-5: Path bandwidth calculation example.....	17
Figure 2-6: Rerouting when the path broken.	19
Figure 2-7: Overview of the on-demand routing algorithm.....	21
Figure 3-1: Architecture.	24
Figure 3-2: Illustration of Hops, Observers, and Interferers.....	25
Figure 3-3: Single Hop.....	26
Figure 3-4: Induction of Single Hop.	27
Figure 3-5: Illustration of available bandwidth analysis.....	28
Figure 3-6: Two-Hop.....	29
Figure 3-7: Induction of Two-Hop.	30
Figure 3-8: Induction of Multi Hop.	31

Figure 3-9: Topology for Table 3.1.	33
Figure 4-1: Topology 1-1.	39
Figure 4-2: Case 1-1 in Single Hop Topology.	40
Figure 4-3: Single Hop CBR Throughput.	40
Figure 4-4: Single Hop VBR Throughput.	41
Figure 4-5: Available Bandwidth Comparison with CBR/VBR Traffic.	41
Figure 4-6: Topology 1-2.	42
Figure 4-7: Case 1-2 in Single Hop Topology.	43
Figure 4-8: Topology 1-3.	43
Figure 4-9: Case 1-3 in Single Hop Topology.	44
Figure 4-10: Topology 1-4.	44
Figure 4-11: Case 1-4 in Single Hop Topology.	45
Figure 4-12: Topology 1-5.	45
Figure 4-13: Case 1-5 in Single Hop Topology.	46
Figure 4-14: Topology 2-1.	47
Figure 4-15: Case 2-1 in Two Hop Topology.	48
Figure 4-16: Two Hop CBR Throughput.	48
Figure 4-17: Two Hop VBR Throughput.	49
Figure 4-18: Available Bandwidth Comparison with CBR/VBR Traffic.	49
Figure 4-19: Topology 2-2.	50
Figure 4-20: Case 2-2 in Two Hop Topology.	51
Figure 4-21: Topology 2-3.	51
Figure 4-22: Case 2-3 in Two Hop Topology.	52
Figure 4-23: Topology 3-1.	53
Figure 4-24: Case 3-1 in Multi Hop Topology.	54

Figure 4-25: Multi Hop CBR Throughput.	54
Figure 4-26: Multi Hop VBR Throughput.	55
Figure 4-27: Available Bandwidth Comparison with CBR/VBR Traffic.	55
Figure 4-28: Topology 3-2.	56
Figure 4-29: Case 3-2 in Multi Hop Topology.....	57
Figure 4-30: Integrated Topology.....	57
Figure 4-31: Average Achieved Throughput Ratio.	58
Figure 4-32: Mean Normalized Delay Time.	59